WS 3915 G

Torch Coolant -20ºC

WS Welding

Technical Data Sheet

Description

WS 3915 G, is a high efficiency coolant specifically formulated and recommended for use in the following applications on Welding and Cutting Torches of all types, even in the most demanding working conditions, increases the life of consumables (torch, hoses, pumps).

Features

- Low viscosity, non-toxic, non-flammable, no Danger pictograms.
- Excellent cooling extending the life of flares, ducts and pumps.
- Lubricates pump, gaskets and seals, prolonging preventive maintenance.
- Protects copper, brass, aluminium and steel from corrosion.
- Environmentally friendly.
- Non-hazardous for storage.
- Excellent thermal stability.
- Outstanding dielectric properties, even in the most demanding equipment.
- It can be used in hot and cold climates.
- Improves weld quality and consistency.
- Reduces electricity consumption.
- Biodegradable and photodegradable, not bioaccumulative.

R-300-73 Ed. 1.0

Applications

Torch Coolant specifically formulated and recommended for:

- MIG welding.
- TIG welding.
- LASER welding.
- LASER cutting.
- PLASMA welding.
- ROBOTIC welding.
- Spot welding.
- Any other welding system requiring a coolant.

Whale Spray S.L
P.I. Ametlla Park.
L'Ametlla del Vallés.
08480 - Barcelona, Spain.
T. : +34 93 882 77 12
whalespray@whalespray.com

WS 3915 G
Torch Coolant -20ºC

WS Welding
Technical Data Sheet

Instructions for use

- Product ready for direct use, no dilution necessary.
- Do not mix with automotive coolants.

Technical Data

Property	Specification/Method	Value
Reference	- - - - -	WS 3915 G
Aspect	- - - - -	Liquid
Colour	- - - - -	Transparent
Density at 20ºC	- - - - -	1.01 kg/l
Conductivity	micros/cm 20ºC	0
Minimum temperature	- - - - -	-20ºC
Maximum temperature	- - - - -	102ºC
Boiling point	- - - - -	102ºC

R-300-73 Ed. 1.0

Whale Spray S.L
P.I. Ametlla Park.
L'Ametlla del Vallés.
08480 - Barcelona, Spain.
T. : +34 93 882 77 12
whalespray@whalespray.com